


HIGH TENSILE STEEL WIRE

99% PURE ZINC GALVANIZING

SPECIAL BONDING AGENT

PVC COATING

Welded Wire Mesh




This PVC-coated galvanized wire is made from hard, drawn, low-carbon steel and galvanized to ASTM standards. The PVC coating is a durable, flexible, fusebonded coating with a minimum thickness of 0.015". All factory-cut ends are sealed prior to shipping.

A wide variety of mesh sizes are available, with many of the popular mesh spacings available from stock (see table below).

Special features such as unequal vertical wire spacing, pigtails, and racking are also available.

	WIRE SIZE		PVC COATED/0	GALVANIZED	304L STAINLESS STEEL		
Spacing of Vertical Wires	Spacing of Horizontal Wires	Gauge of Wire	Wire Diameter (1)	Weight per 100 ft2 (lbs)	Wire Diameter (2)	Weight per 100 ft2 (lbs)	
2"	2"	12	0.135	36	0.105	33	
2"	4"	12	0.135	29.5	0.105	25	
4"	4"	12	0.135	22.5	0.105	17	
4"	8"	12	0.135	16.5	0.105	13	
2"	2"	14	0.11	30	0.08	21.5	
2"	4"	14	0.11	22	0.08	16.5	
4"	4"	14	0.11	14	0.08	11	
4"	8"	14	0.11	11	0.08	8.5	



For more information and quotations, please contact the manufacturer: Riverdale Mills Corporation, 130 Riverdale Street, P.O. Box 200, Northbridge, MA 01534, 1-800-762-6374,

www.riverdale.com

÷	AND LOCATION:	THIS DRAWING IS THE SOLE PROPERTY OF COOLING TOWER DEPOT INC. USE SHALL BE LIMITED TO THE PROJECT FOR WHICH IT IS INTENDED. NO REPRODUCTION SHALL BE MADE KOR SHALL THIS INFORMATION AND DESIGN ARE TO THIND PARTIES WITHOUT THE PRIOR WRITTEN COUSING TOWER DEPOT INC. ANY AND ALL PROPRIETARY WRITS TO THIS INFORMATION AND DESIGN ARE THE SOLE PROPERTY OF COOLING TOWER DEPOT INC.						antin str	0	DRYMIND	
COOLING TOW DEPO	DWG NAME	REV.	REVISIONS	DESIGNED BY:	CHECKED BY:	APPROVED BY:	DATE:	COOLING TOWER DEPOT, INC		Ŭ	A-
	DRAWING NUMBER: JOB NUMBER: SHEET REV:							651 CORPORATE CIRCLE, STE. 206 GOLDEN, CO 80401		1	100
	A-100 1 or 1 0	2						720-746-1234	SCAL	ء _	
Coolina	Tower Depot 651 Corporate Cir	ircle	e Golden, CO 80401 Tol	l Free	877.2	43.39	45	∣ Phone: 720.746.1234 Fax: 720.	<u>746</u>	⊥ 5.111	10